## **Summary Post**

by Mariam Ibrahim Ismail Hasan Almarzoogi - Friday, 17 October 2025, 5:29 PM

In my initial post, I discussed the importance of Agent Communication Languages (ACLs), particularly KQML, in enabling intelligent, meaningful interactions among autonomous agents. Unlike traditional method calls that focus on syntax, ACLs allow agents to express intentions, commitments, and goals through semantically rich performatives, making them ideal for open and heterogeneous environments (Warstadt & Bowman, 2022).

One of the main strengths of ACLs is their interoperability. Agents built on different platforms can still communicate effectively if they follow a shared ACL standard (Kim et al., 2024). This is especially useful in distributed systems like multi-agent simulations, robotics, or smart infrastructure, where coordination is required across independent components. Performatives like "inform" or "request" support deeper semantic interactions (Zhang et al., 2024).

However, I also noted some challenges. ACLs require more computational reasoning and shared ontologies, which can increase system complexity and reduce efficiency in real-time applications (Belda-Medina & Calvo-Ferrer, 2022). In contrast, method invocation in languages like Python or Java is faster and more efficient but lacks the flexibility and semantic depth that ACLs provide (Liu et al., 2024).

This topic helped me understand the trade-offs between flexibility, semantic expressiveness, and computational efficiency. Selecting the appropriate communication method depends heavily on the operational context and system design goals.

## References:

Belda-Medina, J., & Calvo-Ferrer, J. R. (2022). *Using chatbots as AI conversational partners in language learning*. Applied Sciences, 12(17), 8427. https://doi.org/10.3390/app12178427

Kim, C. Y., Lee, C. P., & Mutlu, B. (2024, March). Understanding large-language model (LLM)-powered human-robot interaction. In Proceedings of the 2024 ACM/IEEE International Conference on Human-Robot Interaction (pp. 371–380). https://doi.org/10.1145/3610977.3634966



Liu, N., Chen, L., Tian, X., Zou, W., Chen, K., & Cui, M. (2024). From LLM to conversational agent: A memory-enhanced architecture with fine-tuning of large language models. arXiv preprint arXiv:2401.02777. https://doi.org/10.48550/arXiv.2401.02777



Warstadt, A., & Bowman, S. R. (2022). What artificial neural networks can tell us about human language acquisition. In Algebraic Structures in Natural Language (pp. Press. https://arxiv.org/pdf/2208.07998